24" & 36" Panel Fans

J&D Manufacturing's 24" and 36" Panel Fans have a rugged x-frame mount with an efficient motor and a powerful balanced blade that is designed to create comfortable air velocity.

The cushion-mounted maintenance-free bearings and heavy-duty automatic belt tensioning system on belted models make this fan high performing, low maintenance, and a great value.

Features

- Ships fully assembled ready for installation
- Includes heavy-duty hanging chain kit
- Durable cast iron pulleys on belt drive models
- Balanced high-output prop
- Heavy-duty G90 galvanized 18-gauge venturi
- 36" belt drive models include a heavy-duty spring belt tensioning system
- 24" models have a rigid guard motor mount
- 36" models have X-frame that provides superior strength and rigidity compared to angle iron, square or round tube designs
- Shaft bearings are eccentric locking, pre-lubricated, permanently sealed, rubber mounted for smooth operation and reduced blade fatigue, and are covered by a **Three Year Warranty**
- Wide assortment of optional mounting brackets for wood and steel posts for precise airflow
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings, UL and CUL recognized, and are covered by a **Two Year Warranty**



36" Direct Drive 3-Blade Panel Fan



▲WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.





24" & 36" Panel Fans

Part#	Size	Ph	Spd	Thrust CFM	Thrust CFM/ Watt	Drive	Prop
Single Phase							
VP24	24"	1	1	5,450	15.4	Direct	3-Alm
VP36D	36"	1	1	10,600	20.4	Direct	3-Glv
VP36	36"	1	1	11,030	19.4	Belt	4-Glv
VP36DCA	36"	1	1	10,530	17.5	Direct	3-CA
VP36CA	36"	1	1	10,000	21.4	Belt	3-CA
VP361	36"	1	1	13,000	16.3	Belt	4-Glv
Three Phase							
VP243G	24"	3	1	10,470	22.3	Direct	3-Glv
VP363D	36"	3	1	10,470	22.3	Direct	3-Glv
VP363DCA	36"	3	1	10,650	19.5	Direct	3-CA
VP3631	36"	3	1	13,080	16.6	Belt	4-Glv
VP3631-E	36"	3	1	12,500	18.7	Belt	4-Glv
VP3631CA	36"	3	1	12,040	17.8	Belt	3-CA

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

OSHA requires these fans to be mounted a minimum of 7' above the floor



Installation Options

Direct Drive Fans		Belt Drive Fans						
24"	36"	36"	Part#	Description				
Swi	vel C)ffset	Post Mountir	ng Bracket				
		Χ	VRSBRPR6P	4"-6" Wood Post, Galv.				
Rigid Offset Column Mounting Brackets								
		Χ	VRSBRPR3	3" Column, Black Powder Coat				
		Χ	VRSBRPR35	3½" Column, Black Powder Coat				
		Χ	VRSBRPR4	4" Column, Black Powder Coat				
		Χ	VRSBRPR6	6½" Column, Black Powder Coat				
		Χ	VRSBRSQ6	6" Square Column, Painted				
In-l	In-line Column Mounting Brackets							
Χ	Χ	Χ	VRSBRP3	3"-3½" Column, Black Powder Coat & Galv.				
Χ	Χ	Χ	VRSBRP4	4"-4½" Column, Black Powder Coat & Galv.				
Χ	Χ	Χ	VRSBRP4SQ	3½" Sq. Column, Black Powder Coat & Galv.				
Χ	Χ	Χ	VRSBRP5	5"-5½" Column, Black Powder Coat & Galv.				
X	Χ	Χ	VRSBRP6	6"-61/2" Column, Black Powder Coat & Galv.				
Cha	in Sı	ıspend	ling Kit					
Χ	Χ	Х	HK211	(3) 72" of Chain, w/Fan to Chain Assem. Hrdwr				







▲WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product.

Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.

