

Guards meets

OSHA

equirements

Multi-position

bracket

Poly Chiller™

The Poly Chiller[™] from J&D Manufacturing is an efficient air circulator, great in many environments. The heavy duty motor mount is connected directly to the multi-positional hanging bracket, meaning the poly housing is not part of the support structure so it will not distort like other poly fans.

Features

- Available in 24" and 36"
- Direct drive motor with no belts or bearings to maintain
- Fan ships completely assembled and ready for installation
- Single phase models available pre-wired for 115 or 230 Volts with attached 10' cord with 3-prong plug for no electrician needed installation
- 3-blade galvanized or aluminum prop
- One-piece molded black polyethylene housing WILL NOT RUST
- Multi-position mounting bracket lets you tilt and lock the fan in place
- Round housing shape is easy to clean with no corners for dirt build up
- Heavy duty, corrosion resistant, powder coated brackets, motor mount and guards
- Guards meet OSHA 1910.212(a)(5) requirements and can be mounted at any height
- Totally enclosed, maintenance-free, high-efficiency motors have completely sealed ball bearings, are UL and CUL recognized, and are covered by a Two Year Warranty
- Compatible with our misting/fogging product line

			Thrust	Thrust		
Size	Ph	Spd	CFM	Watt	Drive	Prop
24″	1	1/Var^	4,890	10.9	Direct	3-Alm
36″	1	1	10,120	16.9	Direct	3-Glv
red f	or 1	15V				
24″	1	1/Var^	4,890	10.9	Direct	3-Alm
36″	1	1	10,120	16.9	Direct	3-Glv
red f	or 2	230V				
24″	1	1/Var^	4,890	10.9	Direct	3-Alm
36″	1	1	10,120	16.9	Direct	3-Glv
					·	
24″	3	1	5,240	12.4	Direct	3-Glv
36″	3	1	9,770	19.3	Direct	3-Glv
	24" 36" red f 24" 36" red f 24" 36"	24" 1 36" 1 red for 1 24" 1 36" 1 red for 2 24" 1 36" 1 36" 1	24" 1 1/Var^ 36" 1 1 red for 115V 24" 1 1/Var^ 36" 1 1 red for 230V 24" 1 1/Var^ 36" 1 1 24" 1 1/Var^ 36" 1 1 24" 1 1/Var^ 36" 1 1	24" 1 1/Var^ 4,890 36" 1 1 10,120 red for 115V 24" 1 1/Var^ 4,890 36" 1 1 10,120 10,120 red for 230V 24" 1 10,120 red for 230V 24" 1 10,120 24" 1 1/Var^ 4,890 36" 36" 1 1 10,120 24" 3 1 5,240	Size Ph Spd Thrust CFM CFM/ Watt 24" 1 1/Var^ 4,890 10.9 36" 1 1 10,120 16.9 red for 15/ 1 10,120 16.9 36" 1 1 10,120 16.9 red for 230V 1 1 10,120 16.9 red for 230V 24" 1 1/Var^ 4,890 10.9 36" 1 1 10,120 16.9 16.9 24" 1 1/Var^ 4,890 10.9 36" 36" 1 1 10,120 16.9 16.9 24" 1 1 10,120 16.9 16.9 24" 3 1 5,240 12.4	Size Ph Spd Thrust CFM CFM/ Watt Drive 24" 1 1/Var^ 4,890 10.9 Direct 36" 1 1 10,120 16.9 Direct 24" 1 1/Var^ 4,890 10.9 Direct 24" 1 1/Var^ 4,890 10.9 Direct 36" 1 1 10,120 16.9 Direct 74" 1 1/Var^ 4,890 10.9 Direct 36" 1 1 10,120 16.9 Direct 36" 1 1 5,240 12.4 Direct

Optional Poly Chiller Brackets

/RSBRD36B	Bracket, Poly Chiller, Wall or Post Mount, Black Powder Coat
/RSBRD36C	Bracket, Poly Chiller, 41/2" Column Mount, Black Powder Coat
/RSBRD36SQ	Bracket, Poly Chiller, Square Post Up To 3", Black Powder Coat



Variable speed fans require separate variable speed control to adjust fan speed.

Bold red text is data based on testing performed by an accredited lab using ANSI/AMCA Standard 230-12

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov/product. Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.



Call for FREE Expert Advice, Factory Direct Pricing & Volume Discounts

1-888-849-1233 www.FactoryFansDirect.com