

## VC012 & VC012-C

### Simple Single Stage Dependable Thermostat

J&D Manufacturing's rugged VC012 thermostat is perfect for applications that require a simple control. It may be wired for heating or cooling to control your exhaust fan, circulation fan, power shutter, heater or heat lamp. For plug-and-go operation, the VC012-C is pre-wired with a 115 Volt 8' piggyback cord. Simply plug the thermostat into a grounded outlet, then plug your exhaust fan, circulation fan, or power shutter into the back of the thermostat plug for instant operation. No electrician required!

#### Features

- Rugged UL50 Type 2 enclosure
- Use for heating or cooling
- Large visible dial
- 2.4°F (1.3°C) differential
- Coiled stainless steel sensor provides rapid response to temperature change
- Recalibratable
- UL listed (File# E357053)



Part#	Description	Dial Set Points	Size	Volts	Hz	Amps	Stages
VC012	Single Stage Thermostat	40° to 100°F (5° to 38°C)	4½" x 6¾" x 2½"	120-240	50/60	12/10	1
VC012-C	Single Stage Thermostat with 8' Cord	40° to 100°F (5° to 38°C)	4½" x 6¾" x 2½"	120-240	60	12/10	1

## VC115, VC115-C & VC109

### Single Stage & 2 Stage Moisture Proof Thermostat

J&D Manufacturing's rugged VC115 thermostat is perfect for applications that require a simple weather resistant control. It may be wired for heating or cooling to control your exhaust fan, circulation fan, power shutter, heater or heat lamp. For plug-and-go operation, the VC115-C is pre-wired with a 115 Volt 8' piggyback cord. Simply plug the thermostat into a grounded outlet, then plug your exhaust fan, circulation fan, or power shutter into the back of the thermostat plug for instant operation. No electrician required!

The VC109 is a durable, dual stage thermostat that is ideal for greenhouses, animal confinement buildings, walk-in coolers, freezers, garages, warehouses and any other application requiring a weatherproof mechanical thermostat.

#### Features

- Rugged, weather resistant NEMA 4x enclosure
- Use for heating or cooling
- Large visible dial
- 3°F (1.3°C) differential
- Coiled stainless steel sensor provides rapid response to temperature change
- UL listed (File# E50023)
- CSA certified (#030247\_0\_000)



Part#	Description	Dial Set Points	Size	Volts	Hz	Amps	Stages
VC115	Single Stage Thermostat	40° to 110°F (5° to 43°C)	3" x 6½" x 2½"	115/230/277	50/60	16/12/10	1
VC115-C	Single Stage Thermostat with 8' Cord	40° to 110°F (5° to 43°C)	3" x 6½" x 2½"	115	60	16/12/10	1
VC109	Two Stage Moisture Proof Thermostat	40° to 100°F (5° to 38°C)	3½" x 7" x 5"	115/230/277	50/60	16/12/10	2

**⚠ WARNING:** This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product).

Due to our continual effort to provide the best products available and adhere to market conditions; literature, products, prices and availability are subject to change without notice.